

# VA880

Stereo integrated tube amplifier. 50+50 Watts RMS

|                           |                                           |
|---------------------------|-------------------------------------------|
| <b>Power Tubes</b>        | 4 x KT88                                  |
| <b>Output Stage</b>       | Push-Pull Ultra-linear Class AB1          |
| <b>Power</b>              | 2 x 50 Watts RMS (THD=1%)                 |
| <b>Output</b>             | 4, 8 W Ohms                               |
| <b>Frequency Response</b> | 20Hz - 20KHz (-1dB)                       |
| <b>Feedback</b>           | 7dB                                       |
| <b>Driver Stage</b>       | MOSFET class A                            |
| <b>Preamplifier</b>       | solid-state with mechanical (reed) relays |
| <b>Remote Comtrol</b>     | volume & channel selector                 |
| <b>Inputs</b>             | 4 x line RCA (Cinch)                      |
| <b>Input Sensitivity</b>  | 0.75V <sub>RMS</sub> /47kW (all channels) |
| <b>Power Requirements</b> | 230/115V <sub>AC</sub> , 50/60 Hz         |
| <b>Power Consumption</b>  | 300VA                                     |
| <b>Operating Temp</b>     | 5C° to 40C°                               |
| <b>Weight</b>             | Approx. 20Kg                              |
| <b>Dimensions (wxhxd)</b> | Approx. 38.5x24.5x41.5 cm                 |

